

HS1623RT

GB/CE/ANSI Compliance

HIGHLIGHTS

- Strong off-road performance.
- Rough terrain tyre, large ground clearance, stronger passability.
- Engine drive, more powerful.

Configurations Standard

Automatic Braking	Platform Self-lock Door
Proportional Control	Self-diagnosis
Emergency Descent	Flashing Beacons
Emergency Stop	Tilt Sensor
Extension Platform	Safety Arm
Folding Guardrails	Outriggers
Motion Alarm	Horn
Hour Meter	AC Power to the Platform

Optional

Working Lamp on the Platform
Load Sensing System
Air Pipe to the Platform



Let customers win first

MODEL	HS1623RT
Max.Working Height	17.95m
A-Max. Platform Height(In/out)	15.95m
Platform Dimension (BxC)	3.81X1.81m
Front Platform Extension Length	1.536m
Rear Platform Extension Length	1.238m
D-Heights (Rails Up)	3.21m
Height (Rails Down)	2.44m
E-Length (with Ladder)	4.88m
Overall Width with Outriggers	2.29m
F-Ground Clearance	260mm
G-Wheel Base	2862mm
PERFORMANCE	
Platform Capacity	680kg
Extension Capacity	230kg
Max. Occupancy(in/out)	4/4
Max.Wind Speed	12.5m/s
Drive Height	8.5m
Drive Speed (Stowed)	6.1km/h
Drive Speed (Raised)	1.1km/h
Up/Down Time	55/65s
Turning Radius (Out.)	3.9m
Tilt Rating (Front to Rear/Side to Side)	3°/2°
Gradeability	40%
Max Outrigger Leveling (Front to Rear)	7°
Max Outrigger Leveling (Side to Side)	12°
Tires Size (mm)	33X12-20
POWER	
Engine	Kubota V2403
Drive	4WD
WEIGHT	
Hydraulic Oil Tank Capacity	120L
Fuel Tank Capacity	120L
Weight	7980kg

