

HA09RJE

GB/CE/ANSI Compliance

HIGHLIGHTS

- 1.19m ultra-narrow machine, zero tail swing, suitable for operation in confined space.
- The central layout, good structural rigidity and small yaw of the boom.
- AC motor drive, smooth driving, good micro-motion.
- High-precision platform load sensing system to reduce accidental false alarm shutdown.
- Integrated rotary reducer ensures smooth rotation.
- The machine has zero emissions, smoother operation and more energy saving.
- The platform contactor alarm device to improve safety; the jib can swing $\pm 90^\circ$ to cross obstacles.

Configurations Standard

Horn
Emergency Stop System
Proportional Control
Fault Diagnosis System
Motion Alarm
Overload Sensing System
Flashing Beacons
AC Power to the Platform
Self-lock Gate
Jib Swing
Automatic Leveling Platform
Platform Operation Shield
Electric Emergency Pump
Anti-extrusion device

Optional

Air Tube to the Platform



Let customers win first

| MODEL | HA09RJE |
|-----------------------------|--------------------|
| Max.Working Height | 10.82m |
| Max. Platform Height | 8.82m |
| Max. Horizontal Extension | 6.29m |
| Max.Up and Over Height | 3.77m |
| A- Length (Stowed) | 5.38m |
| B- Width (Stowed) | 1.19m |
| C- Height (Stowed) | 2.04m |
| D- Platform Length | 1.17m |
| E- Platform Width | 0.76m |
| F-Clearance (Stowed) | 0.09m |
| G-Wheel Base | 1.58m |
| PERFORMANCE | |
| Platform Capacity | 230kg |
| Max.Drive Speed (Stowed) | 4.8km/h |
| Gradeability | 35% |
| Turning Radius(In.) | 1.75m |
| Turning Radius(Out.) | 3.35m |
| Turntable Rotation | 355°Non-Continuous |
| Vertical JIB rotation | $\pm 90^\circ$ |
| Platform Rotation | $\pm 90^\circ$ |
| Tail Swing | 0 |
| Tilt Rating | 3° |
| Max.Wind Speed | 12.5m/s |
| POWER | |
| Batteries(V/Ah) | 48V/310Ah |
| Charger | 100-240VAC/13.5A |
| Drive Motor | AC48V |
| Lift Motor | DC48V |
| Hydraulic Oil Tank Capacity | 15L |
| Tires | 24x7x17.5 |
| Auxiliary power | Electric pumps |
| WEIGHT | |
| Weight | 6900kg |

