

HS1218ERT

GB/CE/ANSI Compliance

HIGHLIGHTS

- Drive on all rough terrains.
- Large ground clearance, stronger passability.
- AC motor drive, smooth driving, low noise.
- Large capacity batteries, better endurance.

Configurations Standard

Automatic Braking
Proportional Control
Emergency Descent
Hour Meter
Motion Alarm
Emergency Stop
Extension Platform
Folding Guardrails
AC Power to the Platform

Self-diagnosis
Charging Protection
Flashing Beacons
Tilt Sensor
Safety Arm
Platform Self-lock Door
Horn

Optional

Working Lamp on the Platform
Load Sensing System
Air Pipe to the Platform Outriggers



Let customers win first

MODEL	HS1218ERT
Max.Working Height	14m
A-Max. Platform Height(In/out)	12m
B-Platform Length	2.97m
C-Platform Width	1.65m
Extension Size	0.65m(Double Side)
D-Heights (Rails Up)	2.88m
Height (Rails Down)	2.14m
E-Length (with Ladder)	3.75m
F-Overall Width	1.75m
G-Wheel Base	2.3m
H-Ground Clearance	0.2m
PERFORMANCE	
Platform Capacity	360kg
Extension Capacity	113kg
Max. Occupancy(in/out)	3/2
Max.Drive Speed (Stowed)	4.8km/h
Drive Speed (Raised)	0.6km/h
Turning Radius (In.)	2.29m
Turning Radius (Out.)	4.88m
Up/Down Time	54s/50s
Gradeability	45%
Max. Slope	2°/3°
Control	Proportional Control
Drive	Four-Wheel
Multi Disc Brake	Four-Wheel
Tires (mm)	26X12-16
Max.Wind Speed	12.5m/s
POWER	
Batteries (V/Ah)	48V/310Ah
Charger	100-240VAC/13.5A
WEIGHT	
Weight	5730kg

