

# HS1413E

GB/CE/ANSI Compliance

## HIGHLIGHTS

- Optimized matching, high cycle times, better endurance.
- Precise control greatly improves the smoothness of operating.
- Large ground clearance, stronger passability

## Low Maintenance Cost

- Universal and modular design, easy maintenance.
- Swing out trays of batteries and hydraulic system.
- More durable, stable and safe.

## Configurations Standard

Folding Guardrails	Platform Self-lock Door	Safety Arm
Emergency Stop	Charging Protection	Emergency Descent
Hour Meter	Pothole Protector	Proportional Control
Flashing Beacon	Automatic Braking System	Tilt Sensor
Self-diagnosis	Forklift Hole	Full Height Drive
Extension Platform	Motion Alarm	Horn

## Optional

Load Sensing System  
AC Power to the Platform  
Air Pipe to the Platform



Let customers win first

MODEL	HS1413E
Max. Working Height(In/out)	15.7m/10m
A-Max. Platform Height(In/out)	13.7m/8m
B-Platform Length	2.64m
C-Platform Width	1.12m
Extension Size	0.9m
D-Heights (Rails Up)	2.62m
Height (Rails Down)	2.1m
E-Length (with Ladder)	2.84m
F-Overall Width	1.25m
G-Wheel Base	2.22m
H-Clearance (Stowed)	0.1m
I-Clearance (Raised)	0.02m
PERFORMANCE	
Platform Capacity	250kg
Extension Capacity	113kg
Max. Occupancy(in/out)	2/1
Max.Drive Speed (Stowed)	3.5km/h
Drive Speed (Raised)	0.8km/h
Turning Radius (Out.)	2.3m
Up/Down Time	80/60s
Gradeability	25%
Max. Slope	1.5°/3°
Control	Proportional
Drive	FWD
Multi Disc Brake	Front
Max.Wind Speed	12.5m/s
Tires (mm)	381X127mm
POWER	
Batteries (V/Ah)	24V/300Ah
Lithium battery	24V/280Ah
Charger	100-240VAC/10A
WEIGHT	
Weight	3530kg

