

HT26JE

GB/CE/ANSI Compliance

HIGHLIGHTS

- Eco-friendly, low noise, zero emissions, maintenance-free high-capacity lithium battery
- Industry-leading platform with dual load capacities of 300KG/450KG
- Precise and efficient AC drive system, powerful performance, and smooth control
- Fully electric proportional control, boom can perform compound movements, smooth and efficient, boom weight reduction for energy saving and reduced consumption
- Human-machine interaction interface and self-diagnostic fault system
- Floating bridge design, high passability and off-road capability

Configurations Standard

Horn	Automatic Leveling Platform
Proportional Controls	Fault Diagnosis System
Motion Alarm	Overload Sensing System
Flashing Beacons	Tilt Protection System
Self-lock Gate	Oscillating axle
Emergency Descent System	Color Display
Emergency Stop System	Lithium battery
Anti-extrusion device	

Optional

- AC Power to the Platform
- Air Pipe to the Platform

Let customers win first



MODEL	HT26JE
Max.Working Height	27.9m
Max. Platform Height	25.9m
Max. Horizontal Extension	21.4m
A-Length (Stowed)	12.8m
B-Width (Stowed)	2.49m
C-Heights (Stowed)	2.85m
D- Platform Length	2.44m
E- Platform Width	0.91m
F- Wheelbase	2.85m
G- Ground Clearance	0.32m
Wheel track	2.11m
PERFORMANCE	
Platform Capacity(unrestricted/restricted)	300kg/450kg
Max.Drive Speed (Stowed)	4.8km/h
Gradeability	45%
Turning Radius(In.)	3.28m
Turning Radius(Out.)	6.5m
Turntable Rotation	360°Continuous
Platform Rotation	±90°
Vertical JIB rotation	-60°to 72°
Tilt Rating	5°
Operating Wind Speed	12.5m/s
Tail Swing	1.58m
Lift Motor	24Kw
Drive Motor	5.2Kw
POWER	
Batteries(V/Ah)-Li	80V460AH
Charger	100-240VAC/32A
Tires	385/65-22.5
WEIGHT	
Weight	18450kg
Hydraulic Tank Capacity	170L

