

HA21JE Lead-acid or Lithium

GB/CE/ANSI Compliance

HIGHLIGHTS

- AC motor drive, smooth driving, better micro mobility.
- High-precision overload sensing system to reduce accidental and false alarm shutdown.
- Integrated rotary reducer makes smooth turning, comprehensive protection can adapt to dust environment.
- Large capacity batteries, strong endurance.



Configurations Standard

Horn	Automatic Leveling Platform
Proportional Controls	Fault Diagnosis System
Motion Alarm	Overload Sensing System
Flashing Beacons	Self-lock Gate
Emergency Descent System	Anti-extrusion device
Emergency Stop	Tilt Protection System
Oscillating axle	Color Display
AC Power to the Platform	

Optional

Air Pipe to the Platform

Let customers win first

MODEL	HA21JE
Max.Working Height	22.55m
Max. Platform Height	20.55m
Max. Horizontal Extension	12.5m
Max.Up and Over Height	8.9m
A- Length (Stowed)	9.05m
B- Width (Stowed)	2.49m
C- Height (Stowed)	2.7m
D- Platform Length	2.44m
E- Platform Width	0.91m
F- Wheelbase	2.5m
G- Ground Clearance	0.31m
PERFORMANCE	
Platform Capacity	250kg
Max.Drive Speed (Stowed)	4.8km/h
Gradeability	45%
Turning Radius(In.)	2.42m
Turning Radius(Out.)	5.57m
Turntable Rotation	360°Continuous
Platform Rotation	±90°
H- Turntable Tailswing	0.6
Tilt Rating	5°
Operating Wind Speed	12.5m/s
Lift Motor	11kw
Drive Motor	4X3.3kw
POWER	
Batteries(V/Ah)	48V/440Ah
Lithium battery(Optional)	48V/460Ah
Charger	100-240VAC/16A
Tires	36X14-20
WEIGHT	
Weight	11000kg

