

SPA11T

GB/CE/ANSI Compliance

HIGHLIGHTS

- Simple layout, easy maintenance and upkeep.
- Environmentally friendly, low noise, zero emissions, maintenance-free large-capacity lithium battery.
- Fully electric proportional control, enabling combined movements of the boom;
- Smooth and efficient; boom lowering by self-weight, energy-saving and reduced consumption.
- Dual guide wheel auxiliary walking device.

Configurations Standard

- | | |
|-----------------------------|----------------------------------|
| Auto-Leveling Platform | Hydraulic Outriggers |
| Fault Diagnosis System | Proportional Control |
| Tilt Protection System | Lithium Battery |
| Load Sensing System | Emergency Descent System |
| 2.5-Inch Spherical Tow Hook | Motion Alarm |
| Dual Guide Wheels | Aluminum Alloy Platform |
| Trailer Support Wheel | AC power supply to the platform. |

Optional

Honda GX200 4.8KW auxiliary power.



Let customers win first

MODEL	SPA11T
Maximum Working Height	12.9m
Maximum Platform Height	10.9m
Maximum Horizontal Reach	6.33m
Maximum Overreach Height	5.2m
A-Storage Length	5.65m
B-Storage Width	1.5m
C-Storage Height	2.1m
D-Work Platform Length	1.15m
E-Work Platform Width	0.65m
F-Ground Clearance	0.27m
G-Outrigger Spread Width	3.6m
H-Outrigger Spread Width	3.73m
PERFORMANCE	
Platform Capacity	230kg
Turntable Rotation Angle	360° discontinuous
Platform Oscillation Angle	±90°
Auxiliary Travel Speed	1.5km/h
Towing Speed	80km/h
Tire Model	175R14
POWER	
Battery Capacity	230Ah
WEIGHT	
Total Weight	1840kg

