

HA21JE

GB/CE/ANSI Compliance

HIGHLIGHTS

- AC motor drive, smooth driving, better micro mobility.
- High-precision overload sensing system to reduce accidental and false alarm shutdown.
- Integrated rotary reducer makes smooth turning, comprehensive protection can adapt to dust environment.
- Large capacity batteries, strong endurance.



Configurations Standard

Horn
Proportional Controls
Motion Alarm
Flashing Beacons
Emergency Descent System
Emergency Stop
Oscillating axle

Automatic Leveling Platform
Fault Diagnosis System
Overload Sensing System
Self-lock Gate
Anti-extrusion device
Tilt Protection System
Color Display

Optional

AC Power to the Platform
Air Pipe to the Platform

Let customers win first

MODEL	HA21JE
Max.Working Height	22.55m
Max. Platform Height	20.55m
Max. Horizontal Extension	12.5m
Max.Up and Over Height	8.9m
A- Length (Stowed)	9.05m
B- Width (Stowed)	2.49m
C- Height (Stowed)	2.7m
D- Platform Length	2.44m
E- Platform Width	0.91m
F- Wheelbase	2.5m
G- Ground Clearance	0.31m
PERFORMANCE	
Platform Capacity	250kg
Max.Drive Speed (Stowed)	4.8km/h
Gradeability	45%
Turning Radius(In.)	2.42m
Turning Radius(Out.)	5.57m
Turntable Rotation	360°Continuous
Platform Rotation	±90°
H- Turntable Tailswing	0.6
Tilt Rating	5°
Operating Wind Speed	12.5m/s
Lift Motor	11kw
Drive Motor	3.3kw
POWER	
Batteries(V/Ah)	48V/440Ah
Charger	100-240VAC/16A
Tires	36X14-20
WEIGHT	
Weight	11000kg

