

# HT22JE

GB/CE/ANSI Compliance

## HIGHLIGHTS

- Flexible movement, capable of achieving composite boom movements, with a wide range of operations.
- Four-wheel drive, floating axle design, better passability.
- Integrated rotary reducer makes smooth turning, comprehensive protection can adapt to dust environment.
- High-precision overload sensing system to reduce accidental false alarms and shutdowns.



## Configurations Standard

Horn  
Automatic Leveling Platform  
Proportional Controls  
Fault Diagnosis System  
Overload Sensing System  
Tilt Protection System  
Oscillating axle  
Color Display  
Emergency Stop System

Motion Alarm  
Flashing Beacons  
Self-lock Gate  
Emergency Descent System  
Anti-extrusion device

## Optional

AC Power to the Platform  
Air Pipe to the Platform

Let customers win first

MODEL	HT22JE
Max.Working Height	24m
Max. Platform Height	22m
Max. Horizontal Extension	17m
A-Length (Stowed)	10.9m
B-Width (Stowed)	2.49m
C-Heights (Stowed)	2.77m
D- Platform Length	2.44m
E- Platform Width	0.91m
F- Wheelbase	2.5m
G- Ground Clearance	0.31m
Wheel track	2.1m
PERFORMANCE	
Platform Capacity(unrestricted/restricted)	300kg/450kg
Max.Drive Speed (Stowed)	4.8km/h
Gradeability	45%
Turning Radius(In.)	2.9m
Turning Radius(Out.)	5.5m
Turntable Rotation	360°Continuous
Platform Rotation	±90°
Vertical JIB rotation	-60°to 72°
Tilt Rating	5°
Operating Wind Speed	12.5m/s
H Tail Swing	1.42m
Lift Motor	24kw
Drive Motor	3.3kw
POWER	
Batteries(V/Ah)-Li	80V/368Ah
Charger	100-240VAC/32A
Tires	36X14-20
WEIGHT	
Weight	13000kg
Hydraulic Tank Capacity	170L

