

HT18JE

GB/CE/ANSI Compliance

HIGHLIGHTS

- Environmental friendliness, low noise, zero emission, and maintenance-free large-capacity lithium batteries.
- Precise and efficient AC drive system for strong power and smooth control.
- Smooth and efficient compound boom actions from fully electric proportional control; possible boom lowering with its own weight for energy saving and reduced consumption.
- Human-machine interaction interface and fault self-diagnosis system.
- High gradeability and off-road capability as a result of floating bridge design.



Configurations Standard

- Horn
- Automatic Leveling Platform
- Proportional Controls
- Fault Diagnosis System
- Overload Sensing System
- Tilt Protection System
- Oscillating axle
- Color Display
- Emergency Stop System
- Motion Alarm
- Flashing Beacons
- Self-lock Gate
- Emergency Descent System
- Anti-extrusion device
- AC Power to the Platform

Optional

- Air Pipe to the Platform

Let customers win first

MODEL	HT18JE
Max.Working Height	20.6m
Max. Platform Height	18.6m
Max. Horizontal Extension	12.58m
A-Length (Stowed)	9.72m
B-Width (Stowed)	2.47m
C-Heights (Stowed)	2.73m
D- Platform Length	2.44m
E- Platform Width	0.91m
F- Wheelbase	2.44m
G- Ground Clearance	0.25m
Wheel track	2.2m
PERFORMANCE	
Platform Capacity	320kg
Max.Drive Speed	4.8km/h&0.6km/h
Gradeability	40%
Turning Radius(In.)	3.28m
Turning Radius(Out.)	6.5m
Turntable Rotation	360°Continuous
Platform Rotation	±90°
Tilt Rating	5°
Operating Wind Speed	12.5m/s
H- Turntable Tailswing	1.92m
Hydraulic Tank Capacity	75L
Auxiliary power	12V DC
Lift Motor	3.3kw
Drive Motor	3.3kw
POWER	
Lithium battery	48V/304Ah
Charger	100-240VAC/16A
Tires	33*12-20
WEIGHT	
Weight	8850kg

