

HC1216E-R

GB/CE/ANSI Compliance

HIGHLIGHTS

- Compact structure, light weight, accessible elevators.
- Motor and crawler drive, lower noise, stronger passability.
- Large capacity batteries, better endurance.

Configurations Standard

- | | |
|---------------------|----------------------------|
| Automatic Braking | Emergency Stop Tilt Sensor |
| Extension Platform | Safety Arm |
| Folding Guardrails | Self-diagnosis |
| Charging Protection | Platform Self-lock Door |
| Hour Meter | Flashing Beacons |
| Motion Alarm | Emergency Descent |
| Horn | |

Optional

- Working Lamp on the Platform
- Load Sensing System
- AC Power to the Platform
- Air Pipe to the Platform



Let customers win first

MODEL	HC1216E-R
A-Max. Platform Height(In/out)	11.8m/11.8m
Max. Working Height(In/out)	13.8m/13.8m
B-Platform Length	2.26m
C-Platform Width	1.4m
Extension Size	0.9m
D-Heights (Rails Up)	2.63m
Height (Rails Down)	2.03m
E-Overall Width with Outriggers	2.83m
F-Overall Width	1.6m
G- Ground Clearance	150mm
PERFORMANCE	
Platform Capacity	320kg
Extension Capacity	113kg
Max. Occupancy(in/out)	2/2
Max.Wind Speed	12.5m/s
Drive Speed (Stowed)	2.5km/h
Turning Radius	Rotate in Place
Up/Down Time	65/60s
Gradeability	40%
Max. Slope	/
Leveling angle of the legs	16°/9°
Drive	Rear Crawler
Crawler (mm)	230mmX90mmX53
POWER	
Batteries (V/Ah)	8X6V/200Ah
Charger	100-240VAC/13.5A
WEIGHT	
Weight	3980kg

