

HS1218ERT

GB/CE/ANSI Compliance

HIGHLIGHTS

- Drive on all rough terrains.
- Large ground clearance, stronger passability.
- AC motor drive, smooth driving, low noise.
- Large capacity batteries, better endurance.

Configurations Standard

Automatic Braking
Proportional Control
Emergency Descent
Hour Meter
Motion Alarm
Emergency Stop
Extension Platform
Folding Guardrails

Self-diagnosis
Charging Protection
Flashing Beacons
Tilt Sensor
Safety Arm
Platform Self-lock Door
Horn

Optional

Working Lamp on the Platform
Load Sensing System
AC Power to the Platform
Air Pipe to the Platform Outriggers



Let customers win first

MODEL	HS1218ERT
Max.Working Height	14m
A-Max. Platform Height(In/out)	12m
B-Platform Length	2.97m
C-Platform Width	1.65m
Extension Size	0.65m(Double Side)
D-Heights (Rails Up)	2.88m
Height (Rails Down)	2.14m
E-Length (with Ladder)	3.75m
F-Overall Width	1.75m
G-Wheel Base	2.3m
H-Ground Clearance	0.2m
PERFORMANCE	
Platform Capacity	360kg
Extension Capacity	113kg
Max. Occupancy(in/out)	3/2
Max.Drive Speed (Stowed)	4.8km/h
Drive Speed (Raised)	0.6km/h
Turning Radius (In.)	2.29m
Turning Radius (Out.)	4.88m
Up/Down Time	54s/50s
Gradeability	45%
Max. Slope	2°/3°
Control	Proportional Control
Drive	Four-Wheel
Multi Disc Brake	Four-Wheel
Tires (mm)	26X12-16
Max.Wind Speed	12.5m/s
POWER	
Batteries (V/Ah)	48V/310Ah
Charger	100-240VAC/13.5A
WEIGHT	
Weight	5730kg

