

OPT0408E

GB/CE/ANSI Compliance

HIGHLIGHTS

- Oil-free picking vehicle, pure electricity, zero emission, energy-saving and environmentally friendly.
- Equipped with a multi-level cargo platform to meet material transportation needs.
- Simple layout and easy maintenance and service.
- The two sides of the rotating tray are convenient for maintenance services.
- High precision platform overload sensing system reduces accidental false alarms and shutdowns.

Configurations Standard

- | | |
|-----------------------------------|----------------------------|
| Platform Self-locking Door | Automatic Pit Protection |
| Automatic Braking | System Action Buzzer |
| Emergency Descent System | Full Height Travel |
| Emergency Stop Button | Work Strobe Light |
| Load Sensing System | AC Power to Platform |
| Fault Diagnosis System | Single Extension Platform |
| Tilt Protection System | Charging Protection System |
| Standard Transport Forklift Holes | Horn |



Let customers win first

MODEL	OPT0408E
Max.Working Height	5.85m
A-Max. Platform Height(In/out)	3.85m
B-Length Of Manned Platform	0.76m
C-Width Of Manned Platform	0.57m
D-Heights	1.74m
E-Length	1.63m
F-Overall Width	0.8m
G-Wheel Base	1.2m
H-Clearance	0.05m
I-Pallet Length	0.76m
J-Pallet Width	0.62m
PERFORMANCE	
Minimum Turning Radius (inner wheel/outer wheel)	0m/1.45m
Manned Platform	135kg
Cargo Pallet	90kg
Cargo Deck	115kg
Max. Occupancy	1
Gradeability	15%
DRIVE SPEED	
Folding State Speed	3.5km/h
Lifting Speed	0.6km/h
Ascent/Descent Speed	23/23s
POWER	
Batteries(V/Ah)	24V/100Ah
Charger	100-240VAC/6.3A
Drive Motor	2x24V/0.5kW
Lift Motor	24V/1.4kW
WEIGHT	
Weight	1020kg
TIRE	
Front Wheel	Φ254x62mm
Rear Wheel	Φ305x100mm

