

HS1012H

GB/CE/ANSI Compliance

HIGHLIGHTS

- Optimized matching, high cycle times, better endurance.
- Precise control greatly improves the smoothness of operating.
- Large ground clearance, stronger passability

Low Maintenance Cost

- Universal and modular design, easy maintenance.
- Swing out trays of batteries and hydraulic system.
- More durable, stable and safe.

Configurations Standard

| | | |
|--------------------|--------------------------|----------------------|
| Folding Guardrails | Platform Self-lock Door | Safety Arm |
| Emergency Stop | Charging Protection | Emergency Descent |
| Hour Meter | Pothole Protector | Proportional Control |
| Flashing Beacon | Automatic Braking System | Tilt Sensor |
| Self-diagnosis | Forklift Hole | Full Height Drive |
| Extension Platform | Motion Alarm | Horn |

Optional

Load Sensing System
AC Power to the Platform
Air Pipe to the Platform



Let customers win first

| MODEL | HS1012H |
|--------------------------------|----------------|
| Max. Working Height(In/out) | 11.8m/11.8m |
| A-Max. Platform Height(In/out) | 9.8m/9.8m |
| B-Platform Length | 2.26m |
| C-Platform Width | 1.12m |
| Extension Size | 0.9m |
| D-Heights (Rails Up) | 2.51m |
| Height (Rails Down) | 1.96m |
| E-Length (with Ladder) | 2.49m |
| F-Overall Width | 1.19m |
| G-Wheel Base | 1.87m |
| H-Clearance (Stowed) | 0.1m |
| I-Clearance (Raised) | 0.02m |
| PERFORMANCE | |
| Platform Capacity | 320kg |
| Extension Capacity | 113kg |
| Max. Occupancy(in/out) | 2/1 |
| Max.Drive Speed (Stowed) | 3.5km/h |
| Drive Speed (Raised) | 0.8km/h |
| Turning Radius (Out.) | 2.3m |
| Up/Down Time | 62/39s |
| Gradeability | 25% |
| Max. Slope | 1.5°/3° |
| Control | Proportional |
| Drive | FWD |
| Multi Disc Brake | Rear |
| Tires (mm) | 381mmX127mm |
| Max.Wind Speed | 12.5m/s |
| POWER | |
| Charger | 100-240VAC/10A |
| Lithium battery | 24V/230Ah |
| Batteries (V/Ah) | 24V/200Ah |
| WEIGHT | |
| Weight | 2990kg |

