

# HS2025ERT

GB/CE/ANSI Compliance

## HIGHLIGHTS

- All-terrain and all-road driving.
- Off-road tires with large ground clearance and high gradeability.
- AC motor drive, smooth driving, and excellent inching motion.
- Full-travel load capacity up to 750 kg.
- 48V/620Ah high-capacity battery pack for strong endurance.
- Strong power and flexible manipulation from four-wheel drive and four-way steering.
- 2.7m platform extension for stop at any point and a large operating space.

## Configurations Standard

Automatic Braking System  
Emergency Stop  
Flashing Beacons  
Proportional Control  
Emergency Decent System  
Folding Guardrails  
Safety access support bar  
Hour meter  
Motion Alarm  
Charging Protection System  
Horn

## Optional

Load Sensing System  
AC Power to the Platform



Let customers win first

MODEL	HS2025ERT
Max.Working Height	22m
A-Max. Platform Height(In/out)	20m
B-Platform Length	4.54m
C-Platform Width	2.25m
Extension Size	2.7m
D-Heights (Rails Up)	3.93m
Height (Rails Down)	3.1m
E-Length (with Ladder)	4.94m
F-Overall Width	2.45m
G-Wheel Base	3.2m
H-Ground Clearance	0.4m
PERFORMANCE	
Platform Capacity	750kg
Extension Capacity	750kg
Max. Occupancy(in/out)	4/4
Max.Drive Speed (Stowed)	5.0km/h
Drive Speed (Raised)	0.4km/h
Turning Radius (In.)	1.5m
Turning Radius (Out.)	3.4m
Up/Down Time	90s/75s
Gradeability	30%
Max. Slope	2°/3°
Control	Proportional Control
Drive	Four-Wheel
Multi Disc Brake	Four-Wheel
Tires (mm)	36X14-20
Max.Wind Speed	12.5m/s
POWER	
Lithium battery (V/Ah)	48V/560Ah
Charger	100-240VAC/16A
WEIGHT	
Weight	14550kg

