

# HS0507E

GB/CE/ANSI Compliance

## HIGHLIGHTS

- Double driving efficiency.
- Large platform capacity for different working conditions.
- Multi-disc braking, flexible maneuvering.

## Low Maintenance Cost

- Universal and modular design, easy maintenance.
- Swing out trays of batteries and hydraulic system.
- More durable, stable and safe.

## Configurations Standard

Folding Guardrails	Platform Self-lock Door	Safety Arm
Emergency Stop	Charging Protection	Emergency Descent
Hour Meter	Pothole Protector	Proportional Control
Flashing Beacon	Automatic Braking System	Tilt Sensor
Self-diagnosis	Forklift Hole	Full Height Drive
Extension Platform	Motion Alarm	Horn

## Optional

Load Sensing System  
AC Power to the Platform  
Air Pipe to the Platform

Let customers win first



MODEL	HS0507E
Max. Working Height(In/out)	6.6m/0m
A-Max. Platform Height(In/out)	4.6m/0m
B-Platform Length	1.35m
C-Platform Width	0.7m
Extension Size	0.6m
D-Heights (Rails Up)	2.11m
Height (Rails Down)	1.77m
E-Length (with Ladder)	1.53m
F-Overall Width	0.81m
G-Wheel Base	1.11m
H-Clearance (Stowed)	0.05m
I-Clearance (Raised)	0.02m
PERFORMANCE	
Platform Capacity	230kg
Extension Capacity	113kg
Max. Occupancy(in/out)	2/0
Max.Drive Speed (Stowed)	3.5km/h
Drive Speed (Raised)	0.5km/h
Turning Radius (Out.)	1.7m
Up/Down Time	25/20s
Gradeability	25%
Max. Slope	1.5°/3°
Control	Switch
Drive	RWD
Multi Disc Brake	Rear
Max.Wind Speed	0m/s
Tires (mm)	305X100mm
POWER	
Batteries (V/Ah)	24V/100Ah
Lithium battery	
Charger	100-240VAC/6.3A
WEIGHT	
Weight	995kg

