

HS0607H Lead-acid or Lithium

GB/CE/ANSI Compliance

HIGHLIGHTS

- Optimized matching, high cycle times, better endurance.
- Precise control greatly improves the smoothness of operating.
- Large ground clearance, stronger passability

Low Maintenance Cost

- Universal and modular design, easy maintenance.
- Swing out trays of batteries and hydraulic system.
- More durable, stable and safe.

Configurations Standard

Folding Guardrails	Platform Self-lock Door	Safety Arm
Emergency Stop	Charging Protection	Emergency Descent
Hour Meter	Pothole Protector	Proportional Control
Flashing Beacon	Automatic Braking System	Tilt Sensor
Self-diagnosis	Forklift Hole	Full Height Drive
Extension Platform	Motion Alarm	Horn

Optional

Load Sensing System
AC Power to the Platform
Air Pipe to the Platform



Let customers win first

MODEL	HS0607H
Max. Working Height(In/out)	7.8m/7m
A-Max. Platform Height(In/out)	5.8m/5m
B-Platform Length	1.63m
C-Platform Width	0.74m
Extension Size	0.9m
D-Heights (Rails Up)	2.17m
Height (Rails Down)	1.79m
E-Length (with Ladder)	1.86m
F-Overall Width	0.76m
G-Wheel Base	1.32m
H-Clearance (Stowed)	0.06m
I-Clearance (Raised)	0.02m
PERFORMANCE	
Platform Capacity	230kg
Extension Capacity	113kg
Max. Occupancy(in/out)	2/1
Max.Drive Speed (Stowed)	4km/h
Drive Speed (Raised)	0.8km/h
Turning Radius (Out.)	1.55m
Up/Down Time	16/34s
Gradeability	25%
Max. Slope	1.5°/3°
Control	Proportional
Drive	FWD
Multi Disc Brake	Rear
Tires (mm)	305mmX100mm
Max.Wind Speed	12.5m/s
POWER	
Batteries (V/Ah)	24V/200Ah
Lithium battery	24V/160Ah
Charger	100-240VAC/10A
WEIGHT	
Weight	1560kg

