

HA12RJE

GB/CE/ANSI Compliance

HIGHLIGHTS

- Mid-mounted layout, good structural rigidity, and little boom swing
- AC motor drive, smooth driving, good micro-motion.
- High-precision platform load sensing system to reduce accidental false alarm shutdown.
- Smoother slew ensured by integrated slewing reducer.
- Smoother actions and more energy saving thanks to zero-emission devices
- Platform contact alarm device ensuring higher safety.
- $\pm 80^\circ$ fly jib swing to cross obstacles.

Configurations Standard

Horn
Proportional Control
Motion Alarm
Flashing Beacons
platform self-lock door
Automatic Leveling Platform
Electric Emergency Pump
Emergency Stop
Fault Diagnosis System
Load Sensing System
Flying jib swing
Protective cover for platform operation
Anti-crush device
AC Power to the Platform

Optional

Air Pipe to the Platform



Let customers win first

MODEL	HA12RJE	HA12RJE-Li
Max.Working Height	14.15m	14.15m
Max. Platform Height	12.15m	12.15m
Max. Horizontal Extension	6.83m	6.83m
Max.Up and Over Height	6.54m	6.54m
A- Length (Stowed)	6.16m	6.16m
B- Width (Stowed)	1.5m	1.5m
C- Height (Stowed)	1.92m	1.92m
D- Platform Length	1.17m	1.17m
E- Platform Width	0.76m	0.76m
F-Clearance (Stowed)	0.2m	0.2m
G-Wheel Base	1.96m	1.96m
PERFORMANCE		
Platform Capacity	230kg	230kg
Max.Drive Speed (Stowed)	4.8km/h	4.8km/h
Gradeability	30%	30%
Turning Radius(In.)	0.8m	0.8m
Turning Radius(Out.)	2.3m	2.3m
Turntable Rotation	355°Non-Continuous	355°Non-Continuous
Vertical JIB rotation	$\pm 80^\circ$	$\pm 80^\circ$
Platform Rotation	$\pm 85^\circ$	$\pm 85^\circ$
H- Turntable Tailswing	130mm	130mm
Tilt Rating	3°	3°
Max.Wind Speed	12.5m/s	12.5m/s
POWER		
Batteries(V/Ah)	48V/310Ah	51.2V/280Ah
Charger	100-240VAC/13.5A	100-240VAC/13.5A
Drive Motor	3.3kw	/
Lift Motor	5kw	/
Hydraulic Oil Tank Capacity	19L	/
Tires	22x7x17.5/25.6x7x21	22x7x17.5/25.6x7x21
WEIGHT		
Weight	7100kg	7100kg

