

OPT0408E

GB/CE/ANSI Compliance

HIGHLIGHTS

- Oil-free picking vehicle, pure electricity, zero emission, energy-saving and environmentally friendly.
- Equipped with a multi-level cargo platform to meet material transportation needs.
- Simple layout and easy maintenance and service.
- The two sides of the rotating tray are convenient for maintenance services.
- High precision platform overload sensing system reduces accidental false alarms and shutdowns.

Configurations Standard

Platform Self-locking Door	Automatic Pit Protection
Automatic Braking	System Action Buzzer
Emergency Descent System	Full Height Travel
Emergency Stop Button	Work Strobe Light
Load Sensing System	AC Power to Platform
Fault Diagnosis System	Single Extension Platform
Tilt Protection System	Charging Protection System
Standard Transport Forklift Holes	Horn
GPS	



Let customers win first

MODEL	OPT0408E
Max.Working Height	5.85m
A-Max. Platform Height(In/out)	3.85m
B-Length Of Manned Platform	0.76m
C-Width Of Manned Platform	0.57m
D-Heights	1.74m
E-Length	1.63m
F-Overall Width	0.8m
G-Wheel Base	1.2m
H-Clearance	0.06m
I-Pallet Length	0.76m
J-Pallet Width	0.62m
PERFORMANCE	
Minimum Turning Radius (inner wheel/outer wheel)	0m/1.45m
Manned Platform	135kg
Cargo Pallet	90kg
Cargo Deck	115kg
Max. Occupancy	1
Gradeability	15%
DRIVE SPEED	
Folding State Speed	3.5km/h
Lifting Speed	0.6km/h
Ascent/Descent Speed	23/23s
POWER	
Batteries(V/Ah)	24V/100Ah
Charger	100-240VAC/6.3A
Drive Motor	2x24V/0.5kW
Lift Motor	24V/1.4kW
WEIGHT	
Weight	1020kg
TIRE	
Front Wheel	Φ254x62mm
Rear Wheel	Φ305x100mm

