

HS1413H

GB/CE/ANSI Compliance

HIGHLIGHTS

- Optimized matching, high cycle times, better endurance.
- Precise control greatly improves the smoothness of operating.
- Large ground clearance, stronger passability

Low Maintenance Cost

- Universal and modular design, easy maintenance.
- Swing out trays of batteries and hydraulic system.
- More durable, stable and safe.

Configurations Standard

Folding Guardrails	Platform Self-lock Door	Safety Arm
Emergency Stop	Charging Protection	Emergency Descent
Hour Meter	Pothole Protector	Proportional Control
Flashing Beacon	Automatic Braking System	Tilt Sensor
Self-diagnosis	Forklift Hole	Full Height Drive
Extension Platform	Motion Alarm	Horn

Optional

Load Sensing System
AC Power to the Platform
Air Pipe to the Platform



Let customers win first

MODEL	HS1413H
Max. Working Height(In/out)	15.7m/10m
A-Max. Platform Height(In/out)	13.7m/8m
B-Platform Length	2.64m
C-Platform Width	1.12m
Extension Size	0.9m
D-Heights (Rails Up)	2.62m
Height (Rails Down)	2.1m
E-Length (with Ladder)	2.84m
F-Overall Width	1.25m
G-Wheel Base	2.22m
H-Clearance (Stowed)	0.1m
I-Clearance (Raised)	0.02m
PERFORMANCE	
Platform Capacity	250kg
Extension Capacity	113kg
Max. Occupancy(in/out)	2/1
Max.Drive Speed (Stowed)	3.5km/h
Drive Speed (Raised)	0.8km/h
Turning Radius (Out.)	2.3m
Up/Down Time	80/60s
Gradeability	25%
Max. Slope	1.5°/3°
Control	Proportional
Drive	FWD
Multi Disc Brake	Rear
Tires (mm)	381mmX127mm
Max.Wind Speed	12.5m/s
POWER	
Charger	100-240VAC/10A
Lithium battery	24V/280Ah
Batteries (V/Ah)	24V/300Ah
WEIGHT	
Weight	3530kg

