

HA14JE Lead-acid or Lithium

GB/CE/ANSI Compliance

HIGHLIGHTS

- AC motor drive, smooth driving, better micro mobility, zero tail swing, suitable for operation in narrow spaces.
- High-precision overload sensing system to reduce accidental and false alarm shutdown.
- Integrated rotary reducer makes smooth turning, comprehensive protection can adapt to dust environment.
- Large capacity batteries, strong endurance.



Configurations Standard

Horn	Automatic Leveling Platform
Proportional Controls	Fault Diagnosis System
Motion Alarm	Overload Sensing System
Flashing Beacons	Self-lock Gate
Emergency Descent System	Anti-extrusion device
Emergency Stop	

Optional

AC Power to the Platform
Air Pipe to the Platform

Let customers win first

MODEL	HA14JE	HA14JE-Li
Max. Working Height	16m	16m
Max. Platform Height	14m	14m
Max. Horizontal Extension	7.5m	7.5m
Max. Up and Over Height	7.54m	7.54m
A- Length (Stowed)	6.4m	6.4m
B- Width (Stowed)	1.75m	1.75m
C- Height (Stowed)	1.93m	1.93m
D- Platform Length	1.52m	1.52m
E- Platform Width	0.76m	0.76m
F- Wheelbase	2.01m	2.01m
G- Ground Clearance	0.2m	0.2m
PERFORMANCE		
Platform Capacity	230kg	230kg
Max. Drive Speed (Stowed)	4.8km/h	4.8km/h
Gradeability	30%	30%
Turning Radius(In.)	0.8m	0.8m
Turning Radius(Out.)	3.8m	3.8m
Turntable Rotation	355°	355°
Platform Rotation	±80°	±80°
H- Turntable Tailswing	0	0
Tilt Rating	3°	3°
Operating Wind Speed	12.5m/s	12.5m/s
POWER		
Batteries (V/Ah)	48V/310Ah	51.2V/280Ah
Charger	100-240VAC/13.5A	100-240VAC/13.5A
Tires	705X210X445	705X210X445
WEIGHT		
Weight	7200kg	7200kg
Hydraulic Tank Capacity	20L	20L

